

# Van Steenburgh

Engineering Laboratories, Inc.

Over 15 Years Serving the Industry Worldwide



## **SURE SAFE** **Refrigerant Storage Systems**

Designed for Safety and Convenience in Refrigerant Management

- ✓ Float valve shut-off to prevent overfilling
- ✓ Mechanical safety valve back-up
- ✓ Rubber wheels on roller bearings
- ✓ Powder coated sheet metal
- ✓ UL Approved

### **Specifications**

#### **Pressure Vessels**

6 in. / 15.2 cm OD heat treated mandrel drawn steel; wire welded 10 gauge / 3.4 mm heads; to ASTM, cm ASME and AWS standards

#### **Pressure Test**

Hydrostatically tested to 5 times operating pressure

#### **In/Out Valves**

1/4 in. / 6.35 mm male flares on SS-30, SS-60, and SS-90;  
3/8 in. / 9.5 mm on SS-300

#### **Refrigerants**

R-12, R-22, R-502, R-500 and all alternates in same range

#### **Control Circuit**

120 VAC ; 220 international application upon request

<b><u>Model</u></b>	<b><u>SS-30</u></b>	<b><u>SS-60</u></b>	<b><u>SS-90</u></b>	<b><u>SS-300</u></b>
<b><u>Height</u></b>	39.5 in./100.3 cm	39 in./99.1 cm	51 in./129.5 cm	37 in./93.9 cm
<b><u>Width</u></b>	11 in./27.9 cm	21.5 in./54.6 cm	21.5 in./54.6 cm	42.25 in./106.6 cm
<b><u>Depth</u></b>	17 in./43.1 cm	18 in./45.7 cm	18 in./45.7 cm	24.25 in./61.6 cm
<b><u>Weight</u></b>	56 lbs./25 kg	95 lbs./43 kg	117 lbs./53 kg	337 lbs./153 kg
<b><u>Capacity</u></b> (@75°F/21°C)	30 – 34 lbs. 14 – 15.4 kg	60 – 68 lbs. 27 – 31 kg	90 – 106 lbs. 41 – 48 kg	300 – 311 lbs. 136 – 141 kg
<b><u>Indicator Light</u></b> <b><u>When Full</u></b>	No	Yes	Yes	Yes
<b><u>Moisture</u></b> <b><u>Indicator</u></b>	No	Yes	Yes	Yes

*Distributorships available – contact us today!*